

Steel fireplace LUCY left 12 kW Ø 200

LUCY/12/L/BS EAN: 5901350020142

BGN 3779

The insert with interesting shape and side glass. Thanks to double vision of fire and simple front frame it is designed for the modern home, with unique styling. Such types of inserts are good choice for open spaces where different rooms are connected e.g. living room and dining room.



TECHNICAL DATA

► General

| | |
|--|--|
| Rated output (kW) | 12 |
| Heating power range (kW) | 5.0 - 15 |
| Heating efficiency (%) | 80 |
| Exhaust gas temperature (°C) | 270 |
| Material | steel |
| Fuel type | seasoned hardwood (moisture ≤20%) |
| Max length of logs (cm) | 35 |
| Min outlet grids active field (cm ²) | ≥900 |
| Min inlet grids active field (cm ²) | ≥700 |
| Glazing type | corner |

► Efektywność Energetyczna

| | |
|---------------------------------------|--------------|
| Energy class | A |
| Energy efficiency index (EEI) | 105.4 |
| CO emissions (at 13% O ₂) | 0.1 |

► Physical parameters

| | |
|------------------------------|-------------|
| Weight (kg) | 194 |
| Width (cm) | 69.8 |
| Height (cm) | 127 |
| Depth (cm) | 48 |
| Exhaust outlet diameter (mm) | 200 |

► Certyfikaty/Zgodność

Certifications / Compliance

Compliance with BIMSCHV 2, Designed for recuperation, Meets the criteria of eco-project

2) ≤ given in %

| | |
|--|-----------|
| Dust emission (mg/Nm ³) | 15 |
|--|-----------|

▶ Equipment

Equipment

**Air intake, Ashpan,
Decorative glass glass,
Loading the combustion
chamber**

